

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260412.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

T243,5



24V 3,5A battery charger processor controlled , with step down characteristics

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

T24V 3,5 A Battery Charger

Technical Parameters:

- nominal input voltage: 230V AC, 50Hz , 1.4A
- nominal charging voltage: 24 V DC
- max. charging current: 3,5 A DC
- max. output voltage:
- max. consumption from battery: 50mA
- ambient temperature: -30 +60°C
- operational temperature: max.50°C
- charging characteristics: IUu- 3,5A -28,8V/29,6V-27,2V
- size: 115*160*58mm
- weight: 1,1 kg
- IP class: 44
- Protected against reverse polarity and short circuit.

- Equipped with an additional protection circuit against output overvoltage.